### **HDS 5/12 C**

Unique eco!efficiency mode, simple one-button operation, integrated tanks, on-board practical hose/cable storage, accessory compartment, large wheels and swivel castor – welcome to the hot water compact class!













Order no.

1.272-902.0

■ Economical eco!efficiency mode

Technical data		
EAN code		4054278168845
Current type	Ph / V / Hz	1 / 240 / 50
Flow Rate	l/h	500
Operating pressure	bar / MPa	120 / 12
Temperature (supply 12°C)	°C	max. 80
Power rating	kW	2.9
Consumption fuel oil	kg/h	3.2
Heating oil consumption, ecolefficiency	kg/h	2.6
Power cable	m	5
Fuel tank	1	15
Weight (with accessories)	kg	93.4
Weight incl. packaging	kg	102.2
Dimensions (L × W × H)	mm	1060 × 650 × 920

This device does not require instruction.

Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10 / DN 6, 250 bar
Spray lance	mm	840
SDS system		
Pressure switch control		•
Integral fuel and detergent tank		
Included in delivery.		





#### Efficiency

- ecolefficiency mode economical and environmentally friendly, even during longer neriods of use
- Reduces fuel consumption and CO2 emissions by 20%.
- Accurate detergent dosing unit with clear rinse function.



#### Ease of use

- Intuitive operation with large single-button selector switch.
- Large tank opening with filling chute.



#### Storage

- Lockable accessory compartment for nozzles, tools, etc.
- Storage hooks for power cord and high-pressure hose
- Integrated lance holder for easy transport.





























		Order no.	Description			
TRIGGER GUNS		Order IIO.	Description	_		
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	1		
Conversion kit 1 from high pressure hose	2	4.111-050.0	A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.			
Conversion kit 2 from device	3	4.111-051.0	Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.			
Conversion kit 3 only EASY!Force	4	4.111-052.0	A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.			
SPRAY LANCES						
Rotating spray lances						
Spray lance, 840 mm, rotatable	5	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	-		
LED nozzle light	6	2.680-002.0	LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.			
Spray lance, 250 mm, rotatable	7	4.112-027.0	250 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 400 mm, rotatable	8	4.112-024.0	400 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 600 mm, rotatable	9	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 1050 mm, rotatable	10	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 1550 mm, rotatable	11	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance, 2050 mm, rotatable	12	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.			
Spray lance extender, 1000 mm	13	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.			
Double lance		·		$\vdash$		
Double lance, 960 mm	14	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).			

 $<sup>\</sup>blacksquare$  Included in delivery.  $\qed$  Available accessories.

# **EQUIPMENT FOR HDS 5/12 C 1.272-902.0**





















		1		_
		Order no.	Description	1
SPRAY LANCES				
Angular spray lance		1		
WC and gutter lance	15	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	
Flexible spray lance				
Flexible lance, 1050 mm	16	4.112-035.0	1050 mm flexible lance with variable bend from $20^\circ$ to $140^\circ$ , ideal for cleaning difficult to reach areas, e.g. gutters.	
High pressure articulated joint	17	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	
Gutter cleaner				
Gutter cleaning lance	18	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	
Undercarriage spray lance				
Underbody lance	19	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
Additional handle		ı		Ī
Additional handle for EASY!Lock spray lances	20	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	
PowerControl spray lance				
PowerControl spray lance 034	21	4.112-045.0	The cleaning performance can be adapted to the respective task in an instant. The low pressure mode for the application of the cleaning agent and the adjustment of the jet level round off the product.	
MULTIPLE-JET NOZZLES				
Triple nozzles				
Triple Nozzle, 034	22	4.117-029.0	Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application.	•
HIGH-PRESSURE HOSES				T
Standard with unions on both sides				Г
High-pressure hose, 10 m, DN 6, 250 bar,	23	6.110-034.0	10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun	Ī
2 × EASY!Lock	24	6.110-035.0	connector and manual coupling. Further data: DN 6/155°C/250 bar.	
High-pressure hose, 10 m, DN 6, 300 bar, 2 × EASY!Lock	25	6.110-056.0	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M $22 \times 1.5$ with anti-kink protection. NW $6/155^{\circ}$ C/300 bar	, [
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	26	6.110-031.0	10 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	27	6.110-030.0	15 m high-pressure hose (M $22 \times 1.5$ ) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN $8/155^{\circ}$ C/315 bar.	
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	28	6.110-032.0	20 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	

■ Included in delivery. 

□ Available accessories.

# **EQUIPMENT FOR HDS 5/12 C 1.272-902.0**



















		Order no.	Description	
HIGH-PRESSURE HOSES				t
Standard with unions on both sides				
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	29	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	30	6.110-042.0	15 m high-pressure hose M 22 × 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	31	6.110-043.0	with union on both sides, M 22 $\times$ 1.5 with anti-kink protection. NW 10/155 $^{\circ}$ C/220 bar	
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	32	6.110-044.0		
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	33	6.110-045.0		
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	34	6.110-059.0	22 × 1.5 with anti-kink protection.	
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	35	6.110-060.0		
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	36	6.110-041.0		
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 2 $\times$ EASY!Lock	37	6.110-024.0	1.5 m high-pressure hose (DN 8, M $22 \times 1.5$ ) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M $22 \times 1.5$ ).	
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 1 $\times$ EASY!Lock / 1 $\times$ M22 $\times$ 1.5	38	6.110-069.0	High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.	
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 × EASY!Lock	39	6.110-023.0	With rotary coupling, 2 × M 22 × 1.5	
High-pressure hose Longlife, 20 m, DN 8, 400 bar, $2 \times EASY!Lock$	40	6.110-027.0	with rotary coupling, 2 × M 22 × 1.5	
High-pressure hose Longlife, 15 m, DN 8, 400 bar, $2 \times EASY!Lock$	41	6.110-029.0	With rotary coupling, 2 $\times$ M 22 $\times$ 1.5	
Food industry version with unions on both side	es	1	1	_
High-pressure hose food grade, 15 m, DN 6, 250 bar, 2 × EASY!Lock	42	6.110-063.0	15 m high-pressure hose (DN 6) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. DN 6/155°C/250 bar.	

 $\blacksquare$  Included in delivery.  $\qed$  Available accessories.





















				_
		Order no.	Description	L
HIGH-PRESSURE HOSES				_
Food industry version with unions on both sid	1	L	Lee and the second seco	1.
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	43	6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector.  Non-discolouring outer layer for use in the food industry. M 22 × 1.5 with anti-kink sleeve.	
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	44	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M $22 \times 1.5$ , with kink protection. NW $8/155^{\circ}$ C/250 bar.	
Longlife food industry version with unions on	both	sides		
High-pressure hose food grade Longlife, 10 m, DN 8, 400 bar, $2 \times EASY!Lock$	45	6.110-053.0	With blue, non-marking and animal fat resistant outer covering: durable high-pressure hose (ID 8), 10 m long, ANTI!Twist and EASY!Lock hand screw connection at both ends.	[
High-pressure hose food grade Longlife, 20 m, DN 8, 400 bar, $2 \times EASY!Lock$	46	6.110-054.0	Longlife HP hose for use in the food industry. Außendecke## animal-grease-resistant, non-colour-bleeding material. With patented AVS connection in the pistol (pivot mounted)	[
STROMGENERATOR				Ť
PGG 6/1	47	1.042-208.0		I
ROTARY NOZZLES (DIRT BLASTERS)				Ė
Dirt blaster, large				
Dirt Blaster Nozzle, large, 035	48	4.114-040.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzl and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	e
KÄRCHER POWER NOZZLE				
HP nozzle spray angle 0°				
Power Nozzle 0°, 040	49	2.113-001.0	High-pressure nozzle with powerful jet for extremely stubborn dirt.	
Power nozzle spray angle 15°				
Power Nozzle 15°, 034	50	2.113-042.0	Flat jet nozzle for stubborn dirt.	
Power nozzle spray angle 25°				
Power Nozzle 25°, 034	51	2.113-000.0	Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains	i.
Chemical nozzle , 250	52	2.113-020.0	Brass power nozzle for low-pressure operation and cleaning agent suction.	[
Power nozzle spray angle 40°				Ė
Power Nozzle 40°, 040	53	2.113-003.0	Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces.	
NOZZLE UNION / SPACER				Ė
Nozzle union				
Nozzle screws	54	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	
PIPE CLEANING				Ť
Pipe cleaning hose, ID 6				Ī
Hose assembly TR pipe cleaning DN6 max.2	55	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, DN 6, 20 m, 220 bar	56	6.110-008.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	

 $<sup>\</sup>hfill \square$  Available accessories.



























		1		
		Order no.	Description	
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Hose assembly TR pipe cleaning DN6 max.2	57	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle				
Dirt blaster pipe cleaning D21/040	58	4.765-001.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted	
Dirt blaster pipe cleaning D30/040	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).  The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards jets ensure the necessary forward movement, as well as convenient handling.  Fig. 4.765-004.0  Fig. 6.863-089.0  Fipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.  Fig. 6.863-015.0  Fig. 6.863-015.0  Fig. 6.863-016.0  Fig. 6.863-017.0  Fig. 6.863-017.0			
Nozzle pipe cleaning size 120	60	5.763-089.0	Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	61	5.763-015.0		
	62	5.763-016.0	environmentally-friendly cleaning of blocked drains and pipes.	
	environmentally-friendly cleaning of blocked drains and pipes.			
Rotating pipe cleaning nozzle	64	6.415-428.0		
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Add-on kit hose attachment	65	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	
Add-on kit dirt trap	66	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	
Hard surface cleaner FR 30 ME	•			
FR 30 ME surface cleaner	67	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 450 l/h - 500 l/h	68	2.640-482.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	
Machine-specific nozzle kits for FRV				
Nozzle kit for FRV, 035	69	2.642-430.0	Machine-specific nozzle kit with Kärcher power nozzles and jet nozzle for FRV 30.	
Hard surface cleaner FRV 30 Me				
Extension hose FRV 30 Me and FRV 50 Me	70	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	

<sup>☐</sup> Available accessories.





























		Order no.	Description	
FLOOR AND HARD SURFACE CLEANER				
Hard surface cleaner FRV 30 Me				
FRV 30 Me Surface Cleaner	71	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Basic 1, 350 l/h - 600 l/h	72	4.112-053.0	For high-pressure cleaners with a flow rate of 350-600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	
1-litre cleaning agent container for cup foam lance basic	73	5.071-414.0		
1-litre cleaning agent container for cup foam lance advanced	74	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Cup foam lance Advanced 1, 400 l/h - 600 l/h	75	4.112-063.0		
Cup foam lance DUO Advanced 1, 400 l/h - 600 l/h	76	4.112-067.0		
Inno Foam Set		•		
Inno foam kit with detergent injector	77	2.112-000.0	High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For	
Inno foam kit	78	2.112-008.0	use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set				
Easy Foam Set with RM injector	79	2.112-010.0	HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for	
Easy foam set	80	2.112-011.0	connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set				
Nozzle kit 055 z. Inno/Easy Set 500 - 600 l/h	81	2.111-009.0	Optimal adaptation to different machine outputs for economic use.	
Foam nozzle mounting kit				
Foam nozzle kit	82	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	83	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	
Detergent injector for high pressure	84	4.637-033.0	Cleaning agent dosage at high pressure 3 - 5 %	
☐ Available accessories.		1		

 $<sup>\</sup>hfill\square$  Available accessories.

























		Order no.	Description	
MIXERS AND INJECTORS				
Machine-specific nozzle kit with order no. 3.63	37-170			
Nozzle insert trapezoidal thread HDS-GER	85	4.769-009.0	For HDS 500 - 700 l/h. Consists of nozzle insert + HP power nozzle + union	[
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	86	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Low pressure for units rated up to 1100 l/h	87	4.769-001.0	For low pressure with machines up to 1.100 l/h	
QUICK CONNECT				
Quick-fitting pipe union coupler trapezo	88	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	[
Quick-fitting pipe union plug nipple tra	89	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M $22 \times 1.5$ external thread.	[
DRUM AND TANK CLEANING				
Add-on kit mud sucker	90	2.641-798.0		
OTHER HP ACCESSORIES				
Jet gun	91	2.869-067.0	Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	d [
FLUE PIPE				
Flue gas adapter	92	4.656-149.0	Flue gas adapter with draught damper for flue pipe connection (adapter for HDS burners for	[
	93	4.656-080.0	connection to a stack system).	[
COUPLING PARTS				
Rotary coupling				
Rotary coupling	94	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	[
Connector				
Nozzle connector/screw connector	95	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: $1\times$ M $22\times1.5$ and $1\times$ M $18\times1.5$ .	[
Y distributor	96	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	97	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). No compatible with triple nozzles.	ot
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	98	4.111-029.0	Adapter 1 to connect the old hose with the new hose	- 1

<sup>☐</sup> Available accessories.





























				$\top$
		Order no.	Description	
COUPLING PARTS				
Adapter EASY!Lock				
Adapter 2 M22IG-TR22AG	99	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	100	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter M22 - Swivel	101	4.111-032.0	M22 $\times$ 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	
Adapter 5 TR22IG-M22AG	102	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	103	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	
Adapter 7 M18IG-TR20AG	104	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	105	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	
Coupler -2xM22x1,5	106	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: $2x \ M \ 22 \times 1.5 \ m$ .	
ADAPTER for replacement TR22IG-M22AG Er	107	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	
HOSE REELS		<u> </u>		
Hose reel add-on kit				
Hose reel attachment kit for HDS compact class, 20 m	108	2.110-010.0	Hose reel attachment kit for installation on the machine. For secure and space-saving storage of the high-pressure hoses (with a connection hose for the machine high-pressure outlet).	e 🗆
Automatic, self-winding hose reels				
Automatic plastic hose reel incl. high-pressure hose, 15 $\ensuremath{\mathrm{m}}$	109	2.639-257.0		
Automatic hose reel, powder-coated steel / plastic, 20 m	110	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / synthetic material hose drum, 20 m	111	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated, 20 m	112	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	

<sup>☐</sup> Available accessories.



























		Order no.	Description	
HOSE REELS				Ť
Automatic, self-winding hose reels				
Hose reel, automatic, basalt grey-coated, 20 m	113	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	
Automatic hose reel, stainless steel, includes swivel holder, 20 m	114	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel, 40 m	115	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	116	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	
Stainless steel swivel holder	117	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	[
Anbausatz Schlauchtrommel automatik				
Attachment kit automatic hose reel HDS C	118	2.110-012.0	Complete automatic hose reel attachment kit for HDS compact class. Offers maximum convenience when winding and unwinding the HP hose. Contains: Automatic hose reel, HP hose and all connection parts.	
Attachment kit automatic hose reel holder HDS C	119	2.110-013.0	Holder includes connection material for installing an automatic hose reel to machines from the HDS compact class.	5 [
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	120	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	
Splash guard for roller brush 500	121	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	[
Roller brush 500 soft	122	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	[
Roller brush 500 medium	123	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	[
Roller brush 500 hard	124	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	
Brush hard	125	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	[
Brush medium	126	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	

 $<sup>\</sup>hfill \square$  Available accessories.























		Paradation .		
		Order no.	Description	┙
FACADE AND SOLAR PANEL CLEANING				
Brushes	1			Ļ
Brush soft	127	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kårcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	
Telescopic				
TL low pressure adapter	128	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	
Telescopic lance TL 7 F	129	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	
Telescopic lance TL 7 H	130	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix Telescopic thanks to quick-release fastenings. Up to 7 m reach.	
Telescopic lance TL 10 H	131	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	
Telescopic lance TL 10 C	132	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	
Telescopic lance TL 14 C	133	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	
TL high pressure adapter	134	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	
WET BLASTING ATTACHMENT				Ė
Wet blasting attachment (without nozzle)				Г
Wet blasting attachment with flow control (without nozzles)	135	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	136	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	
Nozzle pack for wet blasting attachment				Ť
Nozzle pack TR wet jet set 0035	137	2.112-021.0	Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment performance. Only in combination with wet blasting attachment 4.115-000.0   4.115-006.0.	
Boron carbide nozzle				Ė
Boron carbide nozzle, for machines as of 1000 l/h	138	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	
ADD-ON KITS				j
Crane lifting kit				Ī
Add-on kit suspension crane HDS C	139	2.642-638.0	Effortless loading by crane.	
				ī
Flame monitoring attachment kit				























		Order no.	Description	
WATER CONNECTION				
Geka coupling				
With hose nozzle, R 1/2"	141	6.388-461.0	with hose liner	
With hose nozzle, R 3/4"	142	6.388-455.0		
With hose nozzle, R 1"	143	6.388-465.0	with hose barb	
Hose coupling	144	6.388-458.0	with female thread	Г
Suction filter				
Water filter	145	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 μm mesh, R 3/4" and R 1" connection, without non-return valve	1 [
Suction filter with check valve	146	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Fine-mesh water filter				
Add-on kit water filter universal	147	2.637-020.0		
Fine-mesh water filter with adapter	148	4.730-102.0	Fine-mesh water filter, 125 $\mu$ m, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter 1".	-,
Fine-mesh water filter, 100 µm, R 1"	149	2.638-270.0	Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protect the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	s [
Water supply hose				Ť
Water supply hose	150	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C	
	151	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	Г
Backflow check valve				
Backflow preventer	152	2.641-374.0	To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. – hot water resistant up to 80 °C – tested according to IEC 60335-2-79 – integrated leakage protection	
WASHING BRUSHES				
Push-on washing brush				
Push-on washing brush	153	4.762-497.0	With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	
Push-on wash brush, M 18 × 1.5	154	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.	

 $<sup>\</sup>hfill\square$  Available accessories.







		Order no.	Description	
WASHING BRUSHES				
Rotating washing brush				
Rotating wash brush for < 800 l/h machines, nylon bristles	155	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to $60^{\circ}$ C. (M $18 \times 1.5$ , replaceable brush insert).	
Rotating wash brush for < 800 l/h machines, natural bristles	156	4.113-003.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to $60^{\circ}$ C, M $18 \times 1.5$ (replaceable brush insert).	

<sup>☐</sup> Available accessories.