HDS 5/11 U

Entry-level, highly portable hot water pressure washer



Made in Germany

0–1 h

EASY!Force

5× LIFETIME FULL CERAMIC VALVE

1 × 360° EASY!Lock

Order no.	1.064-902.0

- Professional entry-level model for mobile applications
- Space-saving upright design
- Flue gas temperature monitor

Technical data		
EAN code		4054278139777
Current type	Ph / V / Hz	1 / 230 – 240 / 50
Flow Rate	l/h	450
Operating pressure	bar / MPa	110 / 11
Power rating	kW	2.2
Consumption fuel oil	kg/h	2.4
Fuel tank	l	6.5
Weight (with accessories)	kg	65.4
Weight incl. packaging	kg	73.6
Dimensions (L × W × H)	mm	618 × 618 × 994

Equipment		
Trigger gun		EASY!Force Advanced
High-pressure hose	m	10
Spray lance	mm	840
Pressure switch control		■

■ Included in delivery.

HDS 5/11 U, 1.064-902.0, 2023-07-26





Innovative upright design

- Effortless transport over landings or stairs.
- Large wheels for unpaved surfaces.



Fine-mesh water filter

- Efficiently protects high-pressure pump against contamination.
- Easy to remove from outside.



Compact design

- Space-saving storage and transport.
- Spill-proof pump and fuel tank for transport lying down.
- Ideal for small service vehicles.

HDS 5/11 U, 1.064-902.0, 2023-07-26

KÄRCHER

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


1


2


3


4


5


6


7


8


9


10


11


12


13


14

		Order no.	Description	
TRIGGER GUNS				
EASY!Force Advanced	1	4.118-005.0	Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.	■
Conversion kit 1 from high pressure hose	2	4.111-050.0	A conversion kit which enables secure connection from an M22 hose onto our innovative EASY!Force trigger gun. The kit includes the EASY!Force Trigger gun, adaptors and lance.	☐
Conversion kit 2 from device	3	4.111-051.0	Provides all the parts required to utilise our EASY!Force technology even on our non-Easy!Force machines. Including adaptors, lance, Easy!Force trigger gun and hose.	☐
Conversion kit 3 only EASY!Force	4	4.111-052.0	A conversion kit for the EASY!Force gun, which includes the correct adaptors to conncect to the M22 style lance and hose.	☐
SPRAY LANCES				
Rotating spray lances				
Spray lance, 840 mm, rotatable	5	4.112-006.0	850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	■
LED nozzle light	6	2.680-002.0	LED work light for assembly on EASY!Force spray lances, providing a clear view in poor lighting conditions ensuring controlled cleaning results.	☐
Spray lance, 250 mm, rotatable	7	4.112-027.0	250 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 400 mm, rotatable	8	4.112-024.0	400 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 600 mm, rotatable	9	4.112-007.0	600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 1050 mm, rotatable	10	4.112-000.0	1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 1550 mm, rotatable	11	4.112-018.0	1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance, 2050 mm, rotatable	12	4.112-021.0	2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure.	☐
Spray lance extender, 1000 mm	13	4.112-048.0	Spray lance extension with EASY!Lock connection. Length 1000 mm.	☐
Double lance				
Double lance, 960 mm	14	2.112-016.0	960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).	☐

■ Included in delivery. ☐ Available accessories.

KÄRCHER

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


15


16


17


18


19


20


21


22


23, 25


24, 26–29

		Order no.	Description	
SPRAY LANCES				
Angular spray lance				
WC and gutter lance	15	4.112-029.0	Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets.	☐
Flexible spray lance				
Flexible lance, 1050 mm	16	4.112-035.0	1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters.	☐
High pressure articulated joint	17	4.112-057.0	For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.	☐
Gutter cleaner				
Gutter cleaning lance	18	2.112-015.0	The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.	☐
Undercarriage spray lance				
Underbody lance	19	4.112-032.0	Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	☐
Additional handle				
Additional handle for EASY!Lock spray lances	20	4.321-380.0	Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task.	☐
PowerControl spray lance				
PowerControl spray lance 034	21	4.112-045.0	The cleaning performance can be adapted to the respective task in an instant. The low pressure mode for the application of the cleaning agent and the adjustment of the jet level round off the product.	☐
MULTIPLE-JET NOZZLES				
Triple nozzles				
Triple Nozzle, 035	22	4.117-030.0	Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For high-pressure cleaners with injector; low-pressure fan jet for detergent removal and application.	■
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 10 m, DN 6, 250 bar, 2 × EASY!Lock	23	6.110-034.0	10 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 6/155°C/250 bar.	■
	24	6.110-035.0		☐
High-pressure hose, 10 m, DN 6, 300 bar, 2 × EASY!Lock	25	6.110-056.0	With patented AVS connection in the trigger gun (pivot-mounted) and hand screw union. M 22 × 1.5 with anti-kink protection. NW 6/155°C/300 bar	☐
High-pressure hose, 10 m, DN 8, 315 bar, 2 × EASY!Lock	26	6.110-031.0	10 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	☐
High-pressure hose, 15 m, DN 8, 315 bar, 2 × EASY!Lock	27	6.110-030.0	15 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	☐
High-pressure hose, 20 m, DN 8, 315 bar, 2 × EASY!Lock	28	6.110-032.0	20 m high-pressure hose (M 22 × 1.5) with kink protection. With patented rotating AVS trigger gun connector and manual coupling. Further data: DN 8/155°C/315 bar.	☐

■ Included in delivery. ☐ Available accessories.

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


24, 26–29


30, 36


31


32–33, 35


34


37


38–40



41


42

		Order no.	Description	
HIGH-PRESSURE HOSES				
Standard with unions on both sides				
High-pressure hose, 30 m, DN 8, 315 bar, 2 × EASY!Lock	29	6.110-014.0	With rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose, 15 m, DN 10, 220 bar, 2 × EASY!Lock	30	6.110-042.0	15 m high-pressure hose M 22 × 1.5) with kink protection and threaded couplings at both ends. Further data: DN 10/155°C/220 bar.	☐
High-pressure hose, 20 m, DN 10, 220 bar, 2 × EASY!Lock	31	6.110-043.0	with union on both sides, M 22 × 1.5 with anti-kink protection. NW 10/155°C/220 bar	☐
High-pressure hose, 25 m, DN 10, 220 bar, 2 × EASY!Lock	32	6.110-044.0		☐
High-pressure hose, 40 m, DN 10, 220 bar, 2 × EASY!Lock	33	6.110-045.0		☐
High-pressure hose, 15 m, DN 12, 210 bar, 2 × EASY!Lock	34	6.110-059.0	High-pressure hose for water volumes greater than 1,800 l / h. With union on both sides. 2x M 22 × 1.5 with anti-kink protection.	☐
High-pressure hose, 40 m, DN 12, 210 bar, 2 × EASY!Lock	35	6.110-060.0		☐
High-pressure hose, 10 m, DN 10, 220 bar, 2 × EASY!Lock	36	6.110-041.0		☐
Longlife 400 with unions on both sides				
High-pressure hose Longlife, 1,5 m, DN 8, 400 bar, 1 × EASY!Lock / 1 × M22 × 1.5	37	6.110-069.0	High-pressure hose (ID 8) with double steel reinforcement, 1.5 m long, suitable for up to 400 bar pressure. Connectors: M 22 × 1.5, quick and convenient EASY!Lock hand screw connection.	☐
High-pressure hose Longlife, 30 m, DN 8, 400 bar, 2 × EASY!Lock	38	6.110-023.0	With rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose Longlife, 20 m, DN 8, 400 bar, 2 × EASY!Lock	39	6.110-027.0	with rotary coupling, 2 × M 22 × 1.5	☐
High-pressure hose Longlife, 15 m, DN 8, 400 bar, 2 × EASY!Lock	40	6.110-029.0	With rotary coupling, 2 × M 22 × 1.5	☐
Food industry version with unions on both sides				
High-pressure hose food grade, 10 m, DN 8, 250 bar, 2 × EASY!Lock	41	6.110-051.0	10 m high-pressure hose (DN 8) with patented (rotating) AVS trigger gun connector. Non-discolouring outer layer for use in the food industry. M 22 × 1.5 with anti-kink sleeve.	☐
High-pressure hose food grade, 20 m, DN 8, 250 bar, 2 × EASY!Lock	42	6.110-052.0	20 m high-pressure hose (DN 8) with swivel coupling. Non-discolouring outer layer for use in the food industry. Connectors at both ends, M 22 × 1.5, with kink protection. NW 8/155°C/250 bar.	☐

■ Included in delivery. ☐ Available accessories.

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


43


44


45


46


47


48–50


51


52


53


54–55


56

		Order no.	Description	
STROMGENERATOR				
PGG 6/1	43	1.042-208.0		☐
ROTARY NOZZLES (DIRT BLASTERS)				
Dirt blaster, large				
Dirt Blaster Nozzle, large, 035	44	4.114-040.0	The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	☐
KÄRCHER POWER NOZZLE				
Power nozzle spray angle 15°				
Power Nozzle 15°, 033	45	2.113-002.0	Flat jet nozzle for stubborn dirt.	☐
Power nozzle spray angle 25°				
Chemical nozzle , 250	46	2.113-020.0	Brass power nozzle for low-pressure operation and cleaning agent suction.	☐
NOZZLE UNION / SPACER				
Nozzle union				
Nozzle screws	47	4.112-011.0	Nozzle screws with protectors for high-pressure and power nozzles	☐
PIPE CLEANING				
Pipe cleaning hose, ID 6				
Hose assembly TR pipe cleaning DN6 max.2	48	6.110-046.0	The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	☐
Pipe cleaning hose, DN 6, 20 m, 220 bar	49	6.110-008.0	20 m flexible high-pressure hose (DN 6) for cleaning pipes up to 220 bar (threaded connection for R 1/8 nozzle).	☐
Hose assembly TR pipe cleaning DN6 max.2	50	6.110-047.0	The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	☐
Pipe cleaning nozzle				
Dirt blaster pipe cleaning D21/040	51	4.765-001.0	The forward-tilted rotating pencil jet removes the most stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	☐
Dirt blaster pipe cleaning D30/040	52	4.765-004.0		☐
Nozzle pipe cleaning size 120	53	5.763-089.0	Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	☐
Pipe cleaning nozzle	54	5.763-015.0	16 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	☐
	55	5.763-016.0		☐
	56	5.763-017.0	30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	☐

☐ Available accessories.

KÄRCHER


EQUIPMENT FOR HDS 5/11 U
1.064-902.0


57


58


59


60


61


62


63


64


65


66


67


68


69


70

		Order no.	Description	
PIPE CLEANING				
Pipe cleaning nozzle				
Rotating pipe cleaning nozzle	57	6.415-428.0	Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	☐
FLOOR AND HARD SURFACE CLEANER				
Hard Surface Cleaner FRV 30				
Add-on kit hose attachment	58	2.642-528.0	Suction cup for fixing the suction hose to smooth surfaces.	☐
Add-on kit dirt trap	59	2.642-532.0	Galvanised steel bucket for collecting coarse dirt and for fixing the suction hose in outside areas.	☐
Hard surface cleaner FR 30 ME				
FR 30 ME surface cleaner	60	2.111-013.0	Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.	☐
Machine-specific nozzle kit for FR				
Nozzle kit for FR, 450 l/h – 500 l/h	61	2.640-482.0	Nozzle kit includes power nozzles and unions. For Kärcher surface cleaners (450 to 500 l/h).	☐
Hard surface cleaner FRV 30 Me				
Extension hose FRV 30 Me and FRV 50 Me	62	4.441-040.0	5 m extension hose for FRV 30 Me. Includes connecting adapter.	☐
FRV 30 Me Surface Cleaner	63	2.111-012.0	Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.	☐
FOAM SYSTEMS				
Cup foam lance				
Cup foam lance Basic 1, 350 l/h – 600 l/h	64	4.112-053.0	For high-pressure cleaners with a flow rate of 350–600 l/h: new, robust and very high-quality foam cup lance with outstanding foam quality while consuming half as much cleaning agent.	☐
1-litre cleaning agent container for cup foam lance basic	65	5.071-414.0		☐
1-litre cleaning agent container for cup foam lance advanced	66	6.414-050.0	Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	☐
Cup foam lance Advanced 1, 400 l/h – 600 l/h	67	4.112-063.0		☐
Cup foam lance DUO Advanced 1, 400 l/h – 600 l/h	68	4.112-067.0		☐
Foam nozzle mounting kit				
Foam nozzle kit	69	2.112-013.0	Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.	☐
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high and low pressure (without nozzles)	70	4.637-032.0	Detergent injector for independent high and low pressure dosage. Maximum dosage about 15%.	☐

☐ Available accessories.

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


71


72


73–74


75


76


77


78


79


80


81


82


83


84

		Order no.	Description	
MIXERS AND INJECTORS				
HP detergent injector				
Detergent injector for high pressure	71	4.637-033.0	Cleaning agent dosage at high pressure 3 – 5 %	☐
Machine-specific nozzle kit with order no. 3.637-170				
Nozzle insert trapezoidal thread HDS-GER	72	4.769-009.0	For HDS 500 – 700 l/h. Consists of nozzle insert + HP power nozzle + union	☐
Nozzle insert with order no. 3.637-001				
Nozzle insert for Order No. 3.637-001, high-pressure for machines up to 1100 l/h.	73	4.769-003.0	Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	☐
Low pressure for units rated up to 1100 l/h	74	4.769-001.0	For low pressure with machines up to 1.100 l/h	☐
QUICK CONNECT				
Quick-fitting pipe union coupler trapezo	75	2.115-000.0	For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 × 1.5 internal thread.	☐
Quick-fitting pipe union plug nipple tra	76	2.115-001.0	Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 × 1.5 external thread.	☐
DRUM AND TANK CLEANING				
Add-on kit mud sucker	77	2.641-798.0		☐
OTHER HP ACCESSORIES				
Jet gun	78	2.869-067.0	Short set-up time, easy transport, instant switch off – the jet gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	☐
COUPLING PARTS				
Rotary coupling				
Rotary coupling	79	4.111-021.0	Kärcher rotary coupling prevents twisting and kinking of high-pressure hoses for ease of use. Connector Easy!Lock. With grip protection.	☐
Connector				
Nozzle connector/screw connector	80	4.111-022.0	Nozzle connector/screw connector for connecting high-pressure nozzles and accessories to the high-pressure trigger gun (with nozzle connector). Connectors: 1x M 22 × 1.5 and 1x M 18 × 1.5.	☐
Y distributor	81	4.111-024.0	Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	☐
Short spray unit	82	4.111-038.0	For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	☐
Adapter EASY!Lock				
Adapter 1 M22AG-TR22AG	83	4.111-029.0	Adapter 1 to connect the old hose with the new hose	☐
Adapter 2 M22IG-TR22AG	84	4.111-030.0	Adapter 2 to connect the old device with the new hose and the old gun with the new hose	☐

☐ Available accessories.

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


85


86


87


88


89


90


91


92


93


94


95


96


97


98

		Order no.	Description	
COUPLING PARTS				
Adapter EASY!Lock				
Adapter 3 M22IG-TR22AG	85	4.111-031.0	Adapter 3 to connect the old gun with the new spray lance and new servo regulator	☐
Adapter M22 – Swivel	86	4.111-032.0	M22 × 1,5female and swivel connection. For extension of high-pressure hoses with AVS connection or for usage of the telescopic lance with a high-pressure hose with AVS connection.	☐
Adapter 5 TR22IG-M22AG	87	4.111-033.0	Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	☐
Adapter 6 TR22IG-M22AG	88	4.111-034.0	Adapter 6 to connect the new device with the old hose and the old hose with the new gun	☐
Adapter 7 M18IG-TR20AG	89	4.111-035.0	Adapter 7 to connect the old spray lance with the new nozzle	☐
Adapter 8 TR20IG-M18AG	90	4.111-036.0	Adapter 8 to connect the new spray lance with the old nozzle	☐
Coupler -2xM22x1,5	91	4.111-037.0	Brass double connector for connecting and extending high-pressure hoses. With rubber protection. Connector: 2x M 22 × 1.5 m.	☐
ADAPTER for replacement TR22IG-M22AG Er	92	4.111-046.0	Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	☐
HOSE REELS				
Automatic, self-winding hose reels				
Automatic plastic hose reel incl. high-pressure hose, 15 m	93	2.639-257.0		☐
Automatic hose reel, powder-coated steel / plastic, 20 m	94	6.392-074.0	Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	☐
Automatic stainless steel / synthetic material hose drum, 20 m	95	6.392-083.0	Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	☐
Automatic hose reel, coated, 20 m	96	6.392-106.0	Automatic hose reel of durable plastic. Painted steel bracket. Suitable for 20 m high-pressure hose.	☐
Hose reel, automatic, basalt grey-coated, 20 m	97	6.392-105.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses.	☐
Automatic hose reel, stainless steel, includes swivel holder, 20 m	98	6.392-076.0	Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	☐

☐ Available accessories.

EQUIPMENT FOR HDS 5/11 U
1.064-902.0

























		Order no.	Description	
HOSE REELS				
Automatic, self-winding hose reels				
Automatic stainless steel hose reel, 40 m	99	6.392-442.0	Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	☐
Powder-coated swivel holder	100	2.639-931.0	Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose. Rotatable 120°. Galvanised steel.	☐
Stainless steel swivel holder	101	2.641-867.0	Swivelling wall bracket made of high-grade steel (for 2.641-866). This makes maximum flexibility and convenience possible when working with the HP hose.	☐
FACADE AND SOLAR PANEL CLEANING				
Brushes				
Drive for roller brush 500	102	4.762-584.0	Hydraulic drive for rotating roller brushes. For cleaning façades or solar power installations with our professional high-pressure cleaners. Installation on spray lance or telescopic lance.	☐
Splash guard for roller brush 500	103	4.762-621.0	Splash guard with velcro fastening for rotating roller brush. Clear view of the brush thanks to transparent film, with protection against splashes at the same time.	☐
Roller brush 500 soft	104	4.762-623.0	Soft brush attachment for use with hydraulic drive (4.762-584.0). Ideal for glass and solar power installation cleaning. Easy quick-change system and secure mounting on drive.	☐
Roller brush 500 medium	105	4.762-624.0	Medium-hard brush attachment for use with hydraulic drive (4.762-584.0). Suitable for sensitive façades, foils and fabrics. Easy and safe quick-change system.	☐
Roller brush 500 hard	106	4.762-625.0	Hard brush attachment for use with hydraulic drive (4.762-584.0). For rough façades, stone and wooden patios. Safe and easy quick-change system.	☐
Brush hard	107	6.960-133.0	Brush with hard bristles for cleaning industry facades and floor coverings and removing coarse dirt. Simple installation on telescopic lances or high-pressure lances from Kärcher.	☐
Brush medium	108	6.960-134.0	Optimally cleans facades, roller shutters and textile fabrics: the brush with medium-hard bristles for fast and simple attachment to telescopic lances or high-pressure lances from Kärcher.	☐
Brush soft	109	6.960-135.0	For simple installation on telescopic lances or high-pressure lances from Kärcher: brush with soft bristles for deep cleaning of sensitive surfaces such as glass or solar systems.	☐
Telescopic				
TL low pressure adapter	110	4.580-097.0	TL low-pressure adapter comprising ball valve for tool-free installation on telescopic lances. Ideal for applications with rotating high-pressure brushes.	☐
Telescopic lance TL 7 F	111	4.762-609.0	Telescopic lance TL 7 F with up to 7 m reach made from robust and lightweight glass fibre. With practical quick-release fasteners for simple retraction and extension.	☐
Telescopic lance TL 7 H	112	4.762-610.0	Multifunctional hybrid telescopic lance TL 7 H made of rigid and lightweight carbon-glass fibre mix. Telescopic thanks to quick-release fastenings. Up to 7 m reach.	☐

☐ Available accessories.

KÄRCHER

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


113–114


115


116


117–118


119


120–122


123


124


126

		Order no.	Description	
FACADE AND SOLAR PANEL CLEANING				
Telescopic				
Telescopic lance TL 10 H	113	4.762-611.0	Up to 10 m reach: hybrid telescopic lance TL 10 H. Comprising carbon-glass fibre mix and suitable for multifunctional use. Simple retraction and extension thanks to quick-release fasteners.	☐
Telescopic lance TL 10 C	114	4.762-612.0	Carbon fibre telescopic lance TL 10 C. With up to 10 m reach and practical quick-release fasteners. Multifunctional use for cleaning facades, windows or solar panels.	☐
Telescopic lance TL 14 C	115	4.762-613.0	Maximum rigidity with minimum weight: telescopic lance TL 14 C made from carbon fibre. Enormous reach of 14 m, multifunctional use and easy to use thanks to quick-release fasteners.	☐
TL high pressure adapter	116	4.775-154.0	TL high-pressure adapter, flexible high-pressure gun for high-pressure cleaning with telescopic lances. Ergonomic, easy to install, suitable for right- and left-handed individuals.	☐
WET BLASTING ATTACHMENT				
Wet blasting attachment (without nozzle)				
Wet blasting attachment with flow control (without nozzles)	117	4.115-000.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet.	☐
Wet blasting attachment without flow control (nozzles not included)	118	4.115-006.0	Paint, rust and scale removal made easy: Kärcher wet blasting attachment with flow control for adding blasting abrasive to the high-pressure jet. Without flow control.	☐
Boron carbide nozzle				
Boron carbide nozzle, for machines as of 1000 l/h	119	6.415-084.0	In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	☐
WATER CONNECTION				
Geka coupling				
With hose nozzle, R 1/2"	120	6.388-461.0	with hose liner	☐
With hose nozzle, R 3/4"	121	6.388-455.0		☐
With hose nozzle, R 1"	122	6.388-465.0	with hose barb	☐
Suction filter				
Water filter	123	6.414-956.0	Suitable for ponds, storage tanks or similar, polyamide filter casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	☐
Suction filter with check valve	124	4.730-012.0	Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	☐
Fine-mesh water filter				
Add-on kit water filter universal	125	2.637-020.0		☐
Fine-mesh water filter with adapter	126	4.730-102.0	Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	☐

☐ Available accessories.

EQUIPMENT FOR HDS 5/11 U
1.064-902.0


127


128


129


130


131


132


133

		Order no.	Description	
WATER CONNECTION				
Water supply hose				
Water supply hose	127	4.440-038.0	NW 13 R1" / R 3/4", up to 30 °C	☐
	128	4.440-207.0	NW 19 R1" / R 3/4", up to 85 °C, for pick-up	☐
Backflow check valve				
Backflow preventer	129	2.641-374.0	To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. – hot water resistant up to 80 °C – tested according to IEC 60335-2-79 – integrated leakage protection	☐
WASHING BRUSHES				
Push-on washing brush				
Push-on washing brush	130	4.762-497.0	With clamp for mounting directly to units' double or triple nozzle. Fits on new double and triple nozzles.	☐
Push-on wash brush, M 18 × 1.5	131	4.113-001.0	Push-on wash brush for universal use. Simply push on to lance. Connector: M 18 × 1.6.	☐
Rotating washing brush				
Rotating wash brush for < 800 l/h machines, nylon bristles	132	4.113-004.0	The rotating wash brush gently removes fine dust and traffic film from all surfaces. Temperature resistant up to 60°C. (M 18 × 1.5, replaceable brush insert).	☐
Rotating wash brush for < 800 l/h machines, natural bristles	133	4.113-003.0	Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to 60°C, M 18 × 1.5 (replaceable brush insert).	☐

☐ Available accessories.